

testo 174T

Mini data logger

The testo 174T mini temperature data logger is ideal for accompanying transports. The logger is simply placed beside the product e.g. in aeroplanes, containers, refrigerated rooms etc. and constantly monitors the fluctuations in temperature unobtrusively.

testo 174T, 1-channel temperature logger with internal sensor (NTC) incl. wall holder, batteries and calibration protocol

Part no.
0572 1560

- Reliable temperature measurement for the monitoring of cold chains and sensitive products in storage and transport
- Easy readout of the data, and transfer to a PC via Testo USB interface



Actual size



Technical data			
Probe type	NTC	Protection class	IP65
Channels	1 x internal	Meas. cycle	1 min - 24 h
Measurement units	°C, °F	Memory	16.000 readings
Measuring range	-30 to +70 °C	Software	ComSoft Basic 5 ComSoft Professional 4
Accuracy	±0.5 °C (-30 to +70 °C)		
Resolution	0.1 °C		
Battery life (at +25 °C)	500 days at 15 min. meas. rate		
Oper. temp.	-30 to +70 °C		
Storage temp.	-40 to +70 °C		
Dimensions	60 x 38 x 18,5 mm		
Battery type	2 x CR 2032 Lithium		

Bundles	Part no.
testo 174T mini data logger set, 1-channel, incl. USB interface for programming and reading out the logger, wall bracket, battery (2 x CR 2032 lithium) and calibration protocol	0572 0561
Accessories	Part no.
testo 174D - USB interface for programming and reading out the loggers testo 174	0572 0500
Battery testo 174 - Lithium button battery CR 2032 for testo 174 (please order two batteries per logger)	0515 0028
Software	
ComSoft Basic 5 - CD ComSoft Basic 5 (if free, registration-mandatory download not wanted)	0572 0580
ComSoft Professional 4 - Pro software incl. data archiving	0554 1704
Calibration Certificates	
ISO temperature calibration certificate; temperature probe; calibration points: -18 °C, 0 °C, +40 °C; per channel/instrument	0520 0153